VP500 Portable Android POS

Enabling the Future of Payments

The VP500 taps into all the advantages Android has to offer. Familiar smartphone-like capabilities enhance customer experience while empowering merchants to modernize and grow their businesses.

Features Android **EMV Contact &** 🕗 Ok × Cancel **Operating System** Contactless 5.5" Touch Screen Signature ۲Ľ · . Capture Screen Display Paper & Digital Text 4G LTE/3G/GPRS | WLAN | or Email Receipts **Bluetooth Wireless Connectivity** Auto-Connection Automatic Software Pav-at-Table Failback Procedure Updates Cash Discounting, **Tip Adjust** 1/3 \$ **Bill Splitting** Dual Pricing, Surcharging Dual-Mid Cash Menu & Inventory **Business** App **Discounting and** * Management Marketplace Interchange+

12:00PM

20 %

Ś

\$33.50

\$5.00

15%

helly audill

Signature

VP500

((•

SALE

Tip Amount

10 %

5%



SPECIFICATIONS



Application Processor		Cortex Quad-core A53, 1.4GHz
Security Processor		ARMv7-M security core, 192MHz
Operating System		Android 10
		1GB RAM, 8GB FLASH
Memory	Optional	2GB RAM, 16GB FLASH
	Optional	Micro SD Card (up to 32GB)
Display		5-inch TFT full color LCD display, resolution of 1280 x 720,
		capacitive multi-touch screen, support electronic signature
Magnetic Card Reader		Triple track, bi-directional, conforming to ISO 7810/7811/7813
Smart Card Reader		EMV L1/L2, conforming to ISO 7816, 1.8V/3V/ 5V, synchronous & asynchronous, T=0 & T=1
Contactless Card Reader		EMV Contactless L1, conforming to ISO 14443 Type A/B, Mifare , Felica
Positioning		GPS, GLONASS, BEIDOU
Wireless Communication		4G / 3G / 2G WIFI (802.11 b/g/n) Bluetooth 2.1/4.2
Audio		1 x Speaker, 1 x Microphone, support audio recording and media play
Keypad		Secure virtual keypad for PIN entry, 1 x power button, 1 x function key
Printer		High-speed thermal printer, 80mm/s Paper roll diameter: 40mm Paper width: 58mm
Camera		2 MP autofocus rear camera with flashlight, support 1D/2D code payment
Peripheral Ports		1 x Micro USB (OTG), 1 x DC Jack
Card Slots		2 x SIM, 1 x SAM, 1 x SD
Battery		Li-ion battery, 7.2V/2600mAh/18.7Wh (Equal to 3.6V/5200mAh)
Power Supply		Input: 100-240V AC 50/60Hz, 0.3A Output: 5.0V DC, 2.0A
Dimensions (L x W x H)		190mm (L) x 81mm (W) x 54.9mm (H)
Weight		440g including battery
		Operating Temperature : $0^{\circ}C \sim 40^{\circ}C(32^{\circ}F^{-}104^{\circ}F)$
Environment		Storage Temperature : -20°C~60°C(-4°F~]40°F)
		Relative Humidity : 5% \sim 93% (Non-condensing)
Certification		PCI PTS 6.x, EMV L1/L2, EMV Contactless L1, PayPass, payWave, American ExpressPay,
		Discover D-PAS, UnionPay QuickPass, JCB, TQM, CE, RoHS

2 Jericho Plaza, Suite 304 Jericho, NY 11753, United States

valorpaytech.com

👎 🕨 🎔 🞯 in

Copyright © 2019-23, Valor PayTech, LLC. All rights reserved.

Reproduction, posting or distribution of this document or its contents is prohibited without the express written consent of Valor PayTech.



Scan to contact Sales Team.

1.800.615.8755

sales@valorpaytech.com

THE FUTURE OF PAYMENT TECHNOLOGY